



Anschlussklemmenplatte, 6-50qmm, 54mm








Powering Business Worldwide™

Typ **BBA-TP3/50**
 Art.-Nr. **107183**

Katalog Nr.

Lieferprogramm

Sortiment			60-mm-System
Grundfunktion			Anschluss- und Verbindungstechnik
Untersortiment			Anschlussklemmenplatten
Werkstoff			Silikonfrei, chlorfrei
Selbstverlöschend			nach UL 94
Kriechstromfestigkeit			CTI 200
Temperaturbeständig			bis 120°C
Beschreibung			Klemmen entfernbar zum Anschließen von ungeschnittenen Leitern Durchschleifen ist möglich
Klemmraum B x H		mm	10 x 15
Breite		mm	54
Pole			3
Bemessungsbetriebsstrom	I_e	A	300
Cu-Schiene		mm	6 - 50 mm ² AWG 10 - AWG 2/0.   6 x 9 x 0.8
Cu-Zahl		kg	0,03
verwendbar für			12 x 5/10 15 x 5/10 20 x 5/10 25 x 5/10 30 x 5/10
verwendbar für			Doppel-T-Profil
Hinweise			
○ Rundleiter eindrätig			
 Rundleiter feindrätig mit fachgerecht verpresster Aderendhülse			
● Rundleiter mehrdrätig			
⚡ Sektorleiter eindrätig			
⚡ Sektorleiter mehrdrätig			
 CU-Band			
 CU-Schiene			

Approbationen

Product Standards
 UL File No.
 UL Category Control No.
 CSA File No.
 CSA Class No.
 North America Certification
 Conditions of Acceptability
 Specially designed for North America
 Suitable for
 Current Limiting Circuit-Breaker
 Max. Voltage Rating
 Degree of Protection

UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
 E300273
 NMTR, NMTR7
 236217
 3211-37
 UL listed, CSA certified
 Refer to approbation report
 No
 Feeder circuits
 Refer to approbation report
 600 V AC
 Feeder circuits

Abmessungen

